




Apex

ADJUSTABLE DOWNLIGHT

Accentuate specific areas or objects with the Apex Adjustable Downlight. To create a versatile family of recessed luminaires, this adjustable downlight is a perfect complement to the Apex Downlight Series. Achieving precise performance and a cohesive design language go hand in hand with the Apex range of luminaires.

- Tilttable up to 45° with its adjustable gimbal
- Rotatable up to 350° for optimum directional flexibility
- An extension of the Apex family of luminaires
- Available with a Pencil (15°), Medium (40°), Wide (60°) or Flood (92°) beam angle

Measurements (mm)



Absolute Luminous Flux

	3000K	4000K
8W (200mA)	530lm	625lm
10W (250mA)	630lm	740m
13W (300mA)	730lm	835lm
15W (350mA)	865lm	990lm

Beam

15° (P) | 40° (M) | 60° (W) | 92° (F)

Apex Series

A comprehensive family of luminaires for every application



Ceiling Recessed
P62

Apex Downlight

Accessories



FL003 (Small)

Frosted Lens (92°)

Finishes

UV Textured Black	
UV Textured White	
Anodised Aluminium	

General Specifications

Material | Powder Coated Aluminium

IP | 65

UGR (Unified Glare Rating) | <19

Warranty | 5 Years

LED

Colour Temp | 2700K, 3000K, 4000K

CRI | 92+

Efficacy | Up to 75lm/w

Colour Deviation | SDCM≤3

Lifetime | >100,000h L70

Driver


Power Factor | >0.90

240V Remote PC Dimmable Driver

Dimming | LED Phase-Cut Dim (PC)


DALI Dim Optional

Photometrics



α = 15°

α = 40°



α = 60°

α = 92° (Frosted)



Driver (DALI drivers can be configured via Product Toolbox)

F

Beam

E

CCT

D

Finish

C

Diameter

B

Product Family

A

F

E

D

C

B

A

Example: AADJ0097.TB30.M-PC020001
Refer to data sheet for available configurations.
Visit Product Toolbox at [unios.com/apexadjustable](https://www.unios.com/apexadjustable) to configure compatible Osram/Tridonic DALI drivers.

Top & Above: Residential application
Above Right: 45° of tiltability



(08) 9248 7388
www.hsreflections.com.au