




Edge

WALL LIGHT

With its unique geometric design, the Edge Wall Light delivers a warm ambience perfect for both interior and exterior applications. Combining a minimalist design and class-leading efficiency, this wall light will add an elegant design touch to any environment.

- Available in a UV textured black, white or anodised aluminium finish
- Elongated forward throw beam is perfect for passageways
- Subtle angular and tapered design creates a geometric statement on any wall or surface

Measurements (mm)




Absolute Luminous Flux

10W (600mA)
745lm (at 3000K)

Beam

40° (M)

Photometrics



$\alpha = 40^\circ$



Finishes

| | |
|--------------------|--|
| UV Textured Black | |
| UV Textured White | |
| Anodised Aluminium | |

General Specifications

| | |
|----------|-------------------------|
| Material | Powder Coated Aluminium |
| IP | 65 |
| Warranty | 3 Years |

LED

| | |
|------------------|---------------|
| Colour Temp | 3000K |
| CRI | 80+ |
| Efficacy | Up to 91lm/w |
| Colour Deviation | SDCM \leq 3 |
| Lifetime | 70,000h L70 |

Driver

| | |
|----------------------------------|---|
| Power Factor | >0.90 |
| 240V Built-in PC Dimmable Driver | DALI Driver must be remote. |
| Dimming | LED Phase-Cut Dim (PC) DALI Dim Optional |



Top: Residential application
Left: Beam angle in application
Above: Precision reflector to deliver a beam perfect for pillars and other outdoor applications

Driver (DALI) drivers can be configured via Product Toolbox
Phase Cut Dimmable Driver included

F

Beam

Medium

M

CCT

30

3000K

D

30

Finish

Textured Black

Textured White

AA

Anodised Aluminium

C

TB

TW

AA

Power

10W

B

0010

Product Family

Edge Wall Light

A

EDGE

F

Driver

E

M

D

30

C

TB

B

0010

A

EDGE

Example: EDGE0010.TB30.M

Refer to data sheet for available configurations.

Visit Product Toolbox at unios.com/edge to configure compatible Osram/Tridonic DALI drivers.



(08) 9248 7388
www.hsreflections.com.au