



Akira

CEILING LIGHT

The Akira Ceiling Light creates an effortless sheet of even light, housed inside a slimline profile. This even diffused light has been meticulously refined to be seamless in a 350mm diameter all the way up to a 900mm diameter. A micro prismatic diffuser completes a ceiling light for applications requiring minimal glare and the gentlest of ambient lighting.

Slimline Profile

A compact and slimline ceiling luminaire that mounts flush to the ceiling with a secure bracket.

Improved Finish

The textured powder coating on the Akira Ceiling is finely tuned for complete evenness and longevity.

Micro Prismatic Diffuser

A perfectly calibrated diffuser is to give a clean, minimal look without sacrificing lumen output and minimising glare (UGR <19).






| A | B | C | D | E | F | Driver |
|------|------|----|----|---|---|-----------------------------------|
| AKIR | 0350 | TB | 30 | F | - | Standard Dimmable Driver included |
| AKIS | 0600 | TW | 40 | F | - | |
| | 0900 | | | F | - | |

Example: AKIR0350.TB30.F
Refer to data sheet for available configurations.
Visit Product Toolbox at unios.com/akira to configure compatible Osram/Tridonic DALI drivers.




Akira Round

The rounded design creates an almost skylight-esque form on the ceiling.

| R350 | R600 | R900 |
|--|---|--|
| Measurements (mm) | Measurements (mm) | Measurements (mm) |
| 55  Ø 350 | 68  Ø 600 | 68  Ø 900 |
| Absolute Luminous Flux | Absolute Luminous Flux | Absolute Luminous Flux |
| 28W (750mA) 2755lm (at 3000K) 3200lm (at 4000K) | 48W (2x 600mA) 3735lm (at 3000K) 4050lm (at 4000K) | 90W (3x 750mA) 7510lm (at 3000K) 7915lm (at 4000K) |
| Beam | Beam | Beam |
| 110° (F) | 110° (F) | 110° (F) |

Akira Square

A square design with subtly beveled corners.

| S350 | S600 | S900 |
|--|---|--|
| Measurements (mm) | Measurements (mm) | Measurements (mm) |
| 55  350x350 | 68  600x600 | 68  900x900 |
| Absolute Luminous Flux | Absolute Luminous Flux | Absolute Luminous Flux |
| 28W (750mA) 2790lm (at 3000K) 2950lm (at 4000K) | 48W (2x 600mA) 3925lm (at 3000K) 4175lm (at 4000K) | 90W (3x 750mA) 8395lm (at 3000K) 8410lm (at 4000K) |
| Beam | Beam | Beam |
| 110° (F) | 110° (F) | 110° (F) |



Dot-Free Illumination

A customised PCB layout of SMDs infused with calculated spacing equates to completely dot-free illumination.



A Versatile Collection

The Akira Ceiling Light is available in round or square and three different sizes for application versatility.



Dimming Capabilities

Rigorous development and testing has resulted in excellent dimming capabilities in all sizes.

Finishes

- UV Textured Black
- UV Textured White

General Specifications

- Material** | Aluminium Trim / Polycarbonate Diffuser
- UGR (Unified Glare Rating)** | <19
- IP** | IP20 (R350 and S350 are IP54)
- Warranty** | 3 Years

LED

- Colour Temp** | 3000K, 4000K
- CRI** | 80+
- Efficacy** | Up to 104lm/w
- Colour Deviation** | SDCM≤3
- Lifetime** | >54,000h L70


Driver

- Power Factor** | >0.90
- 240V Built-in PC Dimmable Driver**
DALI Driver must be remote.
- Dimming** | LED Phase-Cut Dim (PC)
DALI Dim Optional

Notes

- R350 & S350 are Class II connection.
- R600/900 & S600/S900 are Class I connection.

Photometrics



α = 110° (F)



| A | B | C | D | E | F |
|------|------|----|----|---|-----------------------------------|
| AKIR | 0350 | TB | 30 | F | Driver |
| AKIS | 0600 | TW | 40 | F | - |
| AKIR | 0900 | TB | 30 | F | Standard Dimmable Driver included |
| AKIS | 0900 | TW | 40 | F | - |

Example: AKIRO350.TB30.F
Refer to data sheet for available configurations.
Visit Product Toolbox at unios.com/akira to configure compatible Osram/Tridonic DALI drivers.