



LX R56

RECESSED LINEAR LIGHT

1) Mounting Options (specify via sidebar)



Clip System



Spring System

2) Profile



Direct

3) Diffuser




Opal

4) Optional Connection Accessories (specify via sidebar)



15W 90° Connector
(Includes LEDs and power supply)

Measurements (mm)



Beam

120° (F) | Opal

Finishes

Textured Black
Textured White

Custom powder coated finishes available upon request

General Specifications

Material | Powder Coated Aluminium

Weight | 1.05kg/Metre

IP | 40

UGR (Unified Glare Rating) | <22

Warranty | 5 Years

LED

Colour Temp | 2700K, 3000K, 4000K

CRI | 82+

Efficacy | Up to 94lm/w

Colour Deviation | SDCM≤3

Lifetime | 64,000h L70

Driver

Power Factor | >0.90


240V Remote Non-Dimmable Driver

Dimmable remote driver option available

Dimming | 1-10V Dim (AD)

DALI Dim Optional

Photometrics



α = 120° (Opal)



Direct Illumination			
Length (mm)	Cutout (mm)	Power	Absolute Luminous Flux
583	573x47	15W	1255lm
863	853x47	22W	1840lm
1143	1133x47	30W	2510lm
1420	1413x47	38W	3180lm
1703	1693x47	45W	3765lm
1983	1973x47	52W	4350lm
2263	2253x47	60W	5020lm

All absolute luminous flux listed at 4000K

Please email sales@unios.com or call +61 8 9248 1888 for custom lengths and wattages to suit projects.



(08) 9248 7388
www.hsreflections.com.au



Above: Office application
Right: Spring mounting system



A	B	C	D	E	F
LXRC	5605	TB	30	W	-
Example: LXRC5605.TB30.W Refer to data sheet for available configurations. Visit Product Toolbox at unios.com/lxr56 to configure compatible Osram/Tridonic DALI drivers.					
Product Family	Size/Length	Finish	CCT	Beam	Driver (DALI drivers can be configured via Product Toolbox)
LXRS LXRC	5619 5608 5611 5614 5617	TB TW	27 30 40	Flood	-
	1983mm 2263mm L Connector	Textured Black Textured White	2700K 3000K 4000K		Non-dimmable driver is integrated into luminaire - no code is required. For analogue or DALI options please specify via Product Toolbox