

Left & Above:  
Residential application


# Tourmaline

WALL LIGHT

Tourmaline wall sconces emit light in both vertical directions, delivering a warm wall wash of soft light. These fixtures can be custom powder coated, offering limitless architectural design possibilities. Place Tourmaline fixtures to highlight an internal feature wall or use them to draw attention to a vertical portrait or art display.

- Available with a black or white finish with either black, white or gold inset
- Utilise along hallways for soft wall lighting or individually in living areas
- Soft, contoured round corners and an angled inset provide a unique visual aesthetic

### Measurements (mm)



### Absolute Luminous Flux

6W (160mA)

400lm

Beam

40° (M)

### Finishes

Textured Black	
Textured White	
Black/Gold Trim	
White/Gold Trim	

### General Specifications

Material | Powder Coated Aluminium

IP | 20

Warranty | 2 Years

### LED

Colour Temp | 3000K

CRI | 80+

Efficacy | Up to 56lm/w

Colour Deviation | SDCM≤3

Lifetime | 70,000h L70

### Driver

Power Factor | >0.90


240V Built-in PC Dimmable Driver

DALI Driver must be remote.

Dimming | LED Phase-Cut Dim (PC)

DALI Dim Optional

### Photometrics



$\alpha = 40^\circ$



A	B	C	D	E	F	Driver (DALI drivers can be configured via Product Toolbox)												
TOUR	0006	BB	30	M	-	Phase Cut Dimmable Driver included												
<table border="1"> <tr> <td>C</td> <td>Finish</td> <td>BB Textured Black WW Textured White BG Black/Gold Trim WG White/Gold Trim</td> </tr> <tr> <td>D</td> <td>CCT</td> <td>3000K</td> </tr> <tr> <td>E</td> <td>Beam</td> <td>Medium</td> </tr> <tr> <td>F</td> <td></td> <td></td> </tr> </table>							C	Finish	BB Textured Black WW Textured White BG Black/Gold Trim WG White/Gold Trim	D	CCT	3000K	E	Beam	Medium	F		
C	Finish	BB Textured Black WW Textured White BG Black/Gold Trim WG White/Gold Trim																
D	CCT	3000K																
E	Beam	Medium																
F																		
<table border="1"> <tr> <td>B</td> <td>Power</td> <td>6W</td> </tr> <tr> <td>B</td> <td>0006</td> <td>6W</td> </tr> <tr> <td>A</td> <td>Product Family</td> <td>Tourmaline Wall Light</td> </tr> <tr> <td>A</td> <td>TOUR</td> <td>Tourmaline Wall Light</td> </tr> </table>							B	Power	6W	B	0006	6W	A	Product Family	Tourmaline Wall Light	A	TOUR	Tourmaline Wall Light
B	Power	6W																
B	0006	6W																
A	Product Family	Tourmaline Wall Light																
A	TOUR	Tourmaline Wall Light																

Example: **TOUR0006.BB30.M**  
Refer to data sheet for available configurations.  
Visit Product Toolbox at [unios.com/tourmaline](https://unios.com/tourmaline) to configure compatible Osram/Tridonic DALI drivers.